## I-View PM-084R3

Industrial 8.4" TFT Panel Mount LCD Monitor with optional Resistive Touch Screen or Anti Reflective Glass Protection





## **FEATURES**

- 8.4" TFT LCD Panel Display
- High MTBF Backlight up to 30000/50000hrs@ 25°C
- Input Interface: VGA/DVI
- Front Bezel Compliant with IP65 sealing
- Front Bezel Aluminium and Chassis Steel Material
- Mounting Options: Panel Mount or VESA Wall Mount
- Power Input: 12V DC Input, 48W AC/DC Power Adapter
- Optional Resistive 5 wire Touch screen or Anti Reflective Glass Protection


## Introduction

I-View PM-084R3 Industrial Panel Mount TFT LCD Monitor with optional Resistive Touch screen or Anti- Reflective Glass Protection. I-View PM-084R3 offer two different types of input options for different applications.

I-View PM-084R3 is ideal for developing KIOSK, Industrial Test Equipment, Industrial Control systems, Hospital Display, Marine, Defence and ATMs

**Specification** 

LCD			
Model	PM-084R3	PM-084HR3	
LCD Size	8.4"		
Resolution	800x600 (SVGA)	640 x 480 (VGA)	
Brightness	250 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	
Contrast Ratio	600:1		
Viewing Angle	160/140		
Backlight	LED		
Backlight MTBF	30000Hrs	50000Hrs	
LCD Color	262K		
Pixel Pitch (mm)	0.213		
Front Frame Material	Aluminium		
Chassis	Steel		
OSD Function	Yes		
Mounting	Panel Mount/VESA		
Colour	Black		
Input Interface	·		
Input Signal	VGA/DVI		
Touch screen			
Touch screen Type	5 Wire Resistive		
Touch screen Controller	USB/RS-232		
Power Requirement	· · · · · · · · · · · · · · · · · · ·		
DC Input	12V		
Power Supply	48W AC/DC Power Adapter		
Mechanical & Environme	ent		
Dimension	255(W) x 213(H) x 57.8(D) mm		
Weight	Gross 2.5kg		
Operation temperature	0°C to 60°C (32° F to 140° F)		
Storage temperature	-20°C to 80°C (-68° F to 176° F)		
Relative humidity	5% to 95% (Non-Condensing)		
Vibration	5-17Hz 0.1" double amplitude displacement		
	17-640Hz 1.5G Acceleration peak to peak		
Shock	10G acceleration peak to peak (11ms)		
Front Bezel protection	IP65 Compliant		
Ordering Information			
PM-084D1B-C100 Industrial 8.4" TFT 250cd/m² Panel Mount LCD Monitor Anti- Reflective Glass Protection/VGA/DVI Input			
PM-084D1B-C101	Industrial 8.4" TFT 250cd/m² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input		
PM-084D1B-C102	Industrial 8.4" TFT 250cd/m² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input		
PM-084HD1B-C100	Industrial 8.4" TFT 450cd/m² Panel Mount LCD Monitor with Anti- Reflective Glass Protection/VGA/DVI Input		
PM-084HD1B-C101	Industrial 8.4" TFT 450cd/m² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input		
PM-084HD1B-C102	Industrial 8.4" TFT 450cd	Industrial 8.4" TFT 450cd/m² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input	



SINETIC Technologies Pte Ltd, reserves the right to change or update without notice, any information contained herein; to change without notice, the design construction, materials, processing or specifications of any products and to discontinue or limit production or distribution of any products. © 2020 SINETIC Technologies Inc. All rights reserved. DMPM084HD1B Rev 3.0 Dated 202005.