

I-View PM-150R3

Industrial 15" TFT Panel Mount LCD Monitor with optional Resistive Touch Screen or Anti Reflective Glass Protection



Introduction

I-View PM-150R3 Industrial Panel Mount TFT LCD Monitor with optional Resistive Touch screen or Anti-Reflective Glass Protection. I-View PM-150R3 offer three different types of input options for different applications.

I-View PM-150R3 is ideal for developing KIOSK, Industrial Test Equipment, Industrial Control systems, Hospital Display, Marine, Defence and ATMs

Specification

LCD

Model	PM-150R3
LCD Size	15"
Resolution	1024 x 768 (XGA)
Brightness	350 cd/m ²
Contrast Ratio	700:1
Viewing Angle	170/160
Backlight	LED
Backlight MTBF	30000Hrs
LCD Color	16.2M./ 262K
Pixel Pitch (mm)	0.297
Front Frame Material	Aluminium
Chassis	Steel
OSD Function	Yes
Mounting	Panel Mount/VESA
Colour	Black

Input Interface

Input Signal	VGA/DVI
--------------	---------

Touch screen

Touch screen Type	5 Wire Resistive
Touch screen Controller	USB/RS-232

Power Requirement

DC Input	12V
Power Supply	48W AC/DC Power Adapter

Mechanical & Environment

Dimension	379(W) x 303(H) x 57.8(D) mm
Weight	Gross 5kg
Operation temperature	0°C to 60°C (32° F to 140° F)
Storage temperature	-20°C to 80°C (-68° F to 176° F)
Relative humidity	5% to 95% (Non-Condensing)
Vibration	5-17Hz 0.1" double amplitude displacement 17-640Hz 1.5G Acceleration peak to peak
Shock	10G acceleration peak to peak (11ms)
Front Bezel protection	IP65 Compliant

Ordering Information

PM-150R3D1B-C100	Industrial 15" TFT 350cd/m ² Panel Mount LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
PM-150R3D1B-C101	Industrial 15" TFT 250cd/m ² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
PM-150R3D1B-C102	Industrial 15" TFT 350cd/m ² Panel Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input

FEATURES

- 15" TFT LCD Panel Display
- High MTBF Backlight up to 30000hrs@ 25°C
- Input Interface: VGA/DVI
- Front Bezel Compliant with IP65 sealing
- Front Bezel Aluminium and Chassis Steel Material
- Mounting Options: Panel Mount or VESA Wall Mount
- Power Input: 12V DC Input, 48W AC/DC Power Adapter
- Optional Resistive 5 wire Touch screen or Anti Reflective Glass Protection

Dimension

