

I-View CCTV-190R3

Industrial 19" TFT Rack Mount LCD Monitor with optional Resistive Touch Screen or Anti Reflective Glass Protection



FEATURES

- 19" TFT LCD Panel Display
- High MTBF Backlight up to 50000hrs@ 25°C
- Input Interface: VGA/DVI
- Chassis Steel Material
- Mounting Options: Rack Mount or VESA Wall Mount
- Power Input: 12V DC Input, 48W AC/DC Power Adapter
- Optional Resistive 5 wire Touch screen or Anti Reflective Glass Protection

Introduction

I-View CCTV-190R3 Industrial Rack Mount TFT LCD Monitor with optional Resistive Touch screen or Anti-Reflective Glass Protection. I-View CCTV-190R3 offer three different types of input options for different applications.

I-View CCTV-190R3 is ideal for developing KIOSK, Industrial Test Equipment, Industrial Control systems, Hospital Display, Marine, Defence and ATMs.

Specification

LCD	
Model	CCTV-190R3
LCD Size	19"
Resolution	1280x1024 (SXGA)
Brightness	350 cd/m ²
Contrast Ratio	1000:1
Viewing Angle	160/170
Backlight	LED
Backlight MTBF	50000Hrs
LCD Color	16.7M
Pixel Pitch (mm)	0.294
Front Frame Material	Steel
Chassis	Steel
OSD Function	Yes
Mounting	Rack Mount/VESA
Colour	Silver

Input Interface

Input Signal VGA/DVI

Touch screen

Touch screen Type 5 Wire Resistive

Touch screen Controller USB/RS-232

Power Requirement

DC Input 12V

Power Supply 48W AC/DC Power Adapter

Mechanical & Environment

Dimension 482(W) x 355(H) x 50(D) mm

Weight Gross 4.5kg

Operation temperature 0°C to 60°C (32° F to 140° F)

Storage temperature -20°C to 80°C (-68° F to 176° F)

Relative humidity 5% to 95% (Non-Condensing)

Vibration 5-17Hz 0.1" double amplitude displacement
17-640Hz 1.5G Acceleration peak to peak

Shock 10G acceleration peak to peak (11ms)

Front Bezel protection -

Ordering Information

CCTV-190R3D1B-C100	Industrial 19" TFT 350cd/m ² Rack Mount LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
CCTV-190R3D1B-C101	Industrial 19" TFT 350cd/m ² Rack Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
CCTV-190R3D1B-C102	Industrial 19" TFT 350cd/m ² Rack Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input

Dimension

