## **I-View K1768D**





## **Features**

- Integrated KVM with a 17" DVI LCD Monitor, keyboard and mouse in a 1U compact design
- Superior video quality up to 1280 x 1024 @ 60 Hz
- Control up to eight DVI computers
- Combo Interface supports computers with USB keyboards and mouse
- Multiplatform Support-Compatible with Windows, Sun, Unix and Linux
- Convenient computer switching via front panel LEDs, keyboard hotkey combination and OSD(On-Screen Display)
- Auto scan feature for monitoring user-selected computer
- Broadcast mode--operations simultaneously performed on all selected computers
- Hot pluggable --add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server
- Standard rack mount kit and KVM adapter included


## Introduction

The I-View K1768D DVI LCD KVM Switch features an integrated 17" LCD screen, keyboard and touchpad in a single console that occupies only 1U of rack space. It allows access and control up to 8 computers from a single console (keyboard, mouse and monitor). The I-View K1768D LCD KVM Switch has a built-in LCD monitor that supports resolution up to 1280x1024@60Hz. Switching between computers can be easily accomplished by front panel pushbuttons, keyboard hotkey combination or on-screen-display (OSD). The KVM switch supports USB connections for the computers.

Specification		
Model		K1768D
Connections	Direct	8 (DVI-D)
	Max	8
Port Emulation		USB
Compatibility	Multi-platform	Windows, Sun, Unix, Linux
LCD Monitor	LCD Mode	SXGA TFT
	View Area	17"
	Resolution	1280x1024@60Hz
	Display color	16.7 M
	Brightness	250cd/m <sup>2</sup> (Typ)
	Contrast Ratio	1000: 1 (Typ)
	Pixel pitch (mm)	0.264(H) x 0.264(W)
Input Power	, , ,	100V-240V (AC), 50-60Hz, <1.5 A
Optional Power Input		-36V – 72V DC
Power Consumption		21W
Emulation	Keyboard	99 keys (82 keys main keyboard + 17 keys independent small number pad)  Multi-language supportEnglish, Russian, German, French, Korean, Swedish and Italian, etc
	Mouse	X/Y resolution (>1000 points/inch) Supports trackball function
Environment	Operating Temp	0 - 50 °C
Requirement	Storage Temp	-20 - 60 °C
	Humidity	0-80% RH (non-condensing)
Mechanical	Material	SECC
Features	Weight	13.4Kg
	Dimension	448mm x 581mm x 42.5mm

- 1x I-View K1768D LCD Console
- 1x Power Cord (Regional)
- 2x Mounting Rails 8x USB+DVI KVM Cable (1.8m/6ft)
- 1x Quick Start Guide

Ordering Information		
1U 19" Rack Mount 17" LCD, keyboard /Touchpad, USB channel 8 Ports DVI KVM		
765mm x 615mm x 185mm		
1.8m USB DVI KVM Cable		



SINETIC Technologies Inc, reserves the right to change or update without notice, any information contained herein; to change without notice, the design construction, materials, processing or specifications of any products and to discontinue or limit production or distribution of any products. © 2020 SINETIC Technologies Inc. All rights reserved. DMIVIEWK1768D Rev 1.0 Dated 202004.