I-View K1858D

1U 19" Rack Mount 18.5" Wide Screen LCD, keyboard / Touchpad, USB channel 8 Ports **DVI KVM**





Features

- Integrated KVM with a 18.5" DVI LCD Monitor, keyboard and mouse in a 1U compact design
- Superior video quality up to 1920x1080 @ 60 Hz
- Control up to eight DVI computers
- Combo Interface supports computers with USB keyboards and mouse
- Multiplatform Support-Compatible with Windows, Sun, Unix and Linux
- Convenient computer switching via front panel LEDs, keyboard hotkey combination and OSD(On-Screen Display)
- Auto scan feature for monitoring user-selected computer
- Broadcast mode--operations simultaneously performed on all selected computers
- Hot pluggable --add or remove computers without having to power down the switch
- Quickly select your computer by naming the server or inputting SN number of the server
- Standard rack mount kit and KVM adapter included

Introduction


The I-View K1858D DVI LCD KVM Switch features an integrated 18.5" Wide Screen LCD screen, keyboard and touchpad in a single console that occupies only 1U of rack space. It allows access and control up to 8 computers from a single console (keyboard, mouse and monitor). The I-View K1858D LCD KVM Switch has a built-in LCD monitor that supports resolution up to $1920 \times 1080@60$ Hz. Switching between computers can be easily accomplished by front panel pushbuttons, keyboard hotkey combination or on-screen-display (OSD). The KVM switch supports USB connections for the computers.

Specification		
Model		K1858D
Connections	Direct	8 (DVI-D)
	Max	8
Port Emulation		USB
Compatibility	Multi-platform	Windows, Sun, Unix, Linux
LCD Monitor	LCD Mode	FHD TFT
	View Area	18.5"
	Resolution	1920x1080@60Hz
	Display color	16.7 M
	Brightness	500cd/m ² (Typ)
	Contrast Ratio	1000: 1 (Typ)
	Pixel pitch (mm)	0.213(H) x 0.213(W)
Input Power	, ,	100V-240V (AC), 50-60Hz, <1.5 A
Optional Power Input		-36V – 72V DC
Power Consumption		21W
Emulation	Keyboard	99 keys (82 keys main keyboard + 17 keys independent small number pad)
		Multi-language supportEnglish, Russian,
		German, French, Korean, Swedish and
		Italian, etc
	Mouse	X/Y resolution (>1000 points/inch)
		Supports trackball function
Environment	Operating Temp	0 - 50 °C
Requirement	Storage Temp	-20 - 60 °C
-	Humidity	0-80% RH (non-condensing)
Mechanical	Material	SECC
Features	Weight	13.4Ka
	Dimension	448mm x 561mm x 42.5mm

Packaging Content

- 1x I-View K1858D LCD Console
- 1x Power Cord (Regional)
- 2x Mounting Rails 8x USB+DVI KVM Cable (1.8m/6ft)
- 1x Quick Start Guide

Ordering Information		
I-View K1858D	1U 19" Rack Mount 18.5" Wide Screen LCD, keyboard	
	/Touchpad, USB channel 8 Ports DVI KVM	
Packaging	765mm x 615mm x 185mm	
Dimension		
Optional		
CBL-1801D	1.8m USB DVI KVM Cable	



herein; to change without notice, the design construction, materials, processing or specifications of any products and to discontinue or limit production or distribution of any products. © 2020 SINETIC Technologies Inc. All rights reserved. DMIVIEWK1858D Rev 1.0 Dated 202004.