

# I-View™ SS-104

## Industrial 10.4" TFT Stainless Steel wall mount/ Desk mount TFT LCD Monitor with optional Resistive Touch Screen or Anti Reflective Glass Protection



### FEATURES

- 10.4" TFT LCD Panel Display
- High MTBF Backlight up to 35000hrs@ 25°C
- Input Interface: VGA/DVI
- Stainless Steel Material
- Mounting Options: Wall mount/ Desk Mount or VESA Wall Mount
- Power Input: 12V DC Input, 48W AC/DC Power Adapter
- Optional Resistive 5 wire Touch screen or Anti Reflective Glass Protection

### Introduction

I-View™ SS-104 Industrial Stainless Steel wall mount/Desk mount TFT LCD Monitor with optional Resistive Touch screen or Anti Reflective Glass Protection. I-View™ SS-104 offers two different types of input options for different applications.





I-View™ SS-104 is ideal for developing KIOSK, Industrial Test Equipment, Industrial Control systems, Hospital Display, Marine, Defence and ATMs

### Specification

Model	SS-104	SS-104H	SS-104D	SS-104HD
AD Board	D1			
Resolution	800x600 (SVGA)		1024 x 768 (XGA)	
Brightness	350 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>	350 cd/m <sup>2</sup>	1000 cd/m <sup>2</sup>
Contrast Ratio	600:1			
Viewing Angle	140 /120		160/140	
Backlight	LED			
Backlight MTBF	35000Hrs			
LCD Color	262K			
Pixel Pitch (mm)	0.264		0.192	
Front Frame Material	Stainless Steel			
Chassis	Stainless Steel			
OSD Function	Yes			
Mounting	Desk Mount/VESA			
Colour	Stainless Steel			
<b>Input Interface</b>				
Input Signal	VGA/DVI			
Audio Speaker	2W x2			
<b>Touch screen</b>				
Touch screen Type	5 Wire Resistive			
Touch screen Controller	USB/RS-232			
<b>Power Requirement</b>				
AC Input	External AC/DC 12V Power Adapter with universal sensing, AC 90~260V, 50/60hz			
Power Consumption	11Watts			
<b>Mechanical &amp; Environment</b>				
Dimension	262.4(W) x 199.4(H) x 66.0(D) mm			
Weight	NW: 3.0kg GW: 4.0kg			
Operation temperature	0°C to 50°C (32° F to 122° F)			
Storage temperature	-20°C to 80°C (-68° F to 176° F)			
Relative humidity	5% to 95% (Non-Condensing)			
Vibration	5-17Hz 0.1" double amplitude displacement 17-640Hz 1.5G Acceleration peak to peak			
Shock	10G acceleration peak to peak (11ms)			
Front Bezel protection	-			
Dimension	-			

### Ordering Information

SS-104D1-00	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
SS-104D1-01	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
SS-104D1-02	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input
SS-104HD1-00	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
SS-104HD1-01	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
SS-104HD1-02	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input
SS-104DD1-00	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
SS-104DD1-01	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
SS-104DD1-02	Industrial 10.4" TFT 350cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input
SS-104HDD1-00	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with Anti Reflective Glass Protection/VGA/DVI Input
SS-104HDD1-01	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with 5-Wire Resistive Touch Screen (USB)/VGA/DVI Input
SS-104HDD1-02	Industrial 10.4" TFT 1000cd/m <sup>2</sup> Wall mount/ Desk Mount High Resolution LCD Monitor with 5-Wire Resistive Touch Screen (RS-232)/VGA/DVI Input



SINETIC Technologies Inc, reserves the right to change or update without notice, any information contained herein; to change without notice, the design construction, materials, processing or specifications of any products and to discontinue or limit production or distribution of any products. © 2015 SINETIC Technologies Inc. All rights reserved. DMSS104D1 Rev 2.0 Dated 201508.