

RPC-Ci190-N7087

Intel® Core™ i7/i5/i3/Xeon®/Pentium®/Celeron®
Processor Socket 1155 Desktop Processor Q77
Chipset Based 19" LCD Rack Mount PC with 6 USB
2.0/4 USB 3.0/4x COM Ports/VGA /Triple Gigabit
LAN



FEATURES

- Intel® 3rd/2nd Generation Core™ i7/ i5/ i3/ Xeon®/ Pentium®/Celeron® Desktop socket 1155
- Intel® Q77 Express chipset
- Two DDR3 SO-DIMM 1066/1333/1600 MHz up to 16 GB
- One Intel® 82574L Giga LAN and Two Intel® 82579LM Giga LAN
- Intel® Core™ integrated HD Graphics 4000 Technology
- RealTek® ALC888 High-Definition Audio chip on-board
- Multi I/O: 6xUSB 2.0, 4xUSB 3.0, 4x COM ports, 6x SATA
- Expansion: PCIe x16 slot. Supports x1, x4, x8, x16 configurations. & 2x Mini-PCIe sockets
- Bay: 1x Slim SATA DVDRW, 2x 2.5" HDD (Internal) Bays

Introduction

RPC-Ci190-N7087 Industrial Rack Mount PC supporting Intel® Core™ i7/i5/i3/Xeon®/Pentium®/Celeron® Processor Socket 1155 Desktop Processor. RPC-Ci190-N7087 comes with 19" LCD Display. RPC-Ci190X-N7087 supports one Slim DVDRW and Two 2.5" Hard Disk, 4x Com Port, 6 x USB 2.0, 4 x USB 3.0 and one PCIe x16 expansion slot. RPC-Ci190-N7087 is ideal for developing high-performance systems for industrial control and Automation, retail, gaming, print imaging and digital signage.

Specification

Model	RPC-Ci190-N7087
LCD	
Resolution	1280x1024 (SXGA)
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Viewing Angle	178/178
Backlight	LED
Backlight MTBF	35000Hrs
System	
Processor	<ul style="list-style-type: none"> Intel® 3rd/2nd Generation Core™ i7/ i5/ i3/ Xeon®/ Pentium®/Celeron® Desktop socket 1155
BIOS	<ul style="list-style-type: none"> uEFI BIOS. 64Mbit FlashROM with DOS and Windows update utility support.
System Memory	<ul style="list-style-type: none"> Two DDR3 1066/1333/1600 SO-DIMM up to 16 GB
Chipset	<ul style="list-style-type: none"> Intel® Q77 Express chipset
Video	<ul style="list-style-type: none"> Intel® Core i processors integrated HD graphics engine. VGA, HDMI, DisplayPort on rear I/O. One 40-pins connector to support up to dual-24bits LVDS LCD
Ethernet	<ul style="list-style-type: none"> One Intel® 82574L & Two Intel® 82579LM Gigabit Ethernet Controller Support Wake-on-LAN, Remote Boot with PXE and RTL.
On Board I/O	<ul style="list-style-type: none"> Four serial ports as COM1~COM4. COM1 is RS232/422/485 selectable by jumper with auto-flow control. Two SATA-III and four SATA-II ports support IDE, AHCI, RAID. Support four USB3.0 ports. Two ports are on rear I/O. Support six USB2.0 ports. Two ports are on rear I/O. One Parallel port supports SPP/ECP/EPP mode. 16bits Digital I/O One SMBus interface PS2 KB and MS.
Watchdog Timer	<ul style="list-style-type: none"> Programmable watchdog timer for 1~255 seconds.
CMOS	<ul style="list-style-type: none"> On-board RTC with 242 bytes of Battery-back CMOS RAM.
Audio	<ul style="list-style-type: none"> RealTek ALC888 High-Definition Audio chip on-board. Support Line-OUT, Line-IN, MIC, SPDIF, CD-IN and Surrounding sounds with pin-headers.
Power	<ul style="list-style-type: none"> One 20pins power connector for system power. One ATX-12V 4-pins connector for CPU power. Support both AT and ATX mode.
Cooling	<ul style="list-style-type: none"> One CPU cooling FAN connector nearby CPU socket One system cooling FAN connectors for chassis or power supply cooling.
Power Requirement	
Power Supply	<ul style="list-style-type: none"> Industrial Auto Range 300W Power Supply
Mechanical & Environment	
Drive Bay	<ul style="list-style-type: none"> One Slim DVDRW & Two 2.5" Hard Disk Bays
Dimension	<ul style="list-style-type: none"> 484(W) x 400(H) x 113(D) mm
Weight	<ul style="list-style-type: none"> Gross 15kg
Operation temperature	<ul style="list-style-type: none"> 0°C to 60°C (32° F to 140° F)
Storage temperature	<ul style="list-style-type: none"> -20°C to 80°C (-68° F to 176° F)
Relative humidity	<ul style="list-style-type: none"> 5% to 95% (Non-Condensing)
Vibration	<ul style="list-style-type: none"> 5-17Hz 0.1" double amplitude displacement 17-640Hz 1.5G Acceleration peak to peak
Shock	<ul style="list-style-type: none"> 10G acceleration peak to peak (11ms)
Additional Chassis FAN	-
Front Bezel protection	<ul style="list-style-type: none"> IP65 Compliant

Ordering Information

RPC-Ci190-N7087-C100	Intel® Core™ i7/i5/i3/Xeon®/Pentium®/Celeron® Processor Socket 1155 Desktop Processor Q77 Chipset Based 19" LCD Rack Mount PC 300cd/m ² with 6 USB 2.0/4 USB 3.0/4x COM Ports/VGA /Triple Gigabit LAN, 300W Power Supply ARG Protection and Sensor & Slim Socket 1155 CPU Cooler
RPC-Ci190-N7087-C101	Intel® Core™ i7/i5/i3/Xeon®/Pentium®/Celeron® Processor Socket 1155 Desktop Processor Q77 Chipset Based 19" LCD Rack Mount PC 300cd/m ² with 6 USB 2.0/4 USB 3.0/4x COM Ports/VGA /Triple Gigabit LAN, 300W Power Supply/USB Touch Screen Controller and Sensor & Slim Socket 1155 CPU Cooler
RPC-Ci190-N7087-C102	Intel® Core™ i7/i5/i3/Xeon®/Pentium®/Celeron® Processor Socket 1155 Desktop Processor Q77 Chipset Based 19" LCD Rack Mount PC 300cd/m ² with 6 USB 2.0/4 USB 3.0/4x COM Ports/VGA /Triple Gigabit LAN, 300W Power Supply/RS-232 Touch Screen Controller and Sensor & Slim Socket 1155 CPU Cooler

Dimension

