

SC-M608-R3

Industrial ATX Motherboard Compact Chassis



FEATURES

- Compact chassis supports up to 7 add-on Cards (Depend on the Motherboard)
- Two 5.25" and One 3.5" disk drives
- Front accessible USB interface for easy data transfer
- Front-accessible filtered cooling fan provide optimized and streamlined airflow
- Front LEDs indicate power status, and HDD activity
- Supports 400W single PS/2 and Mini redundant ATX power supplies

Introduction

Industrial ATX Motherboard Compact Chassis supports Standard ATX Motherboard. SC-M608R3 can support up to 3 Drives. Single 9cm system cooling fan allows maximum ventilation for the system to function at its peak.

SC-M608R2 supports only Standard PS/2 Power Supplies.

Specification

System	
Drive bays	Totally 3 drive bay: 2x 5.25" CD and 1 x 3.5" HDD bay Drive bay equipped with anti-vibration function
Front Panel	Two USB 2.0 ports at front bezel
Motherboard	ATX Motherboard
Fan	One 90mm intake fan
Power Supply	PS2 or hot swappable redundant P/S (Option)
Expansion	7 Slot for ATX Motherboard
Color	Beige/Black
Dimension	410(D) x 310(W) x 175(H)mm
Weight	N.W: 8.1 KG.W:9.1 KGS

Mechanical & Environment

Operating Temperature	0°~50°C
Storage Temperature	-40°~70°C
Relative Humidity	5~95%, non-condensing
Storage Humidity	5% ~ 95%
Altitude	10,000 Feet (3000 m)
Vibration (Operating)	1.5G Max
Shock	10G peak acceleration (10Msec duration)

Ordering Information

SC-M608R3-C0	Industrial ATX Motherboard Compact Chassis (Color:Beige)
SC-M608R3-C1	Industrial ATX Motherboard Compact Chassis (Color:Black)

Optional

TCPS1D41Y060	Industrial 600W ATX PS/2 Auto Ranging Power Supply
TCPS1D41Y050	Industrial 500W ATX PS/2 Auto Ranging Power Supply
TCPS1D41Y040	Industrial 400W ATX PS/2 Auto Ranging Power Supply

Dimension

