

# SC-M604-R3

## Industrial uATX Motherboard Compact Chassis



### FEATURES

- Compact chassis supports up to 4 add-on Cards (Depend on the Motherboard)
- Two 5.25" External and One 3.5" disk drives
- Front accessible USB interface for easy data transfer
- Front-accessible filtered cooling fan provide optimized and streamlined airflow
- Front LEDs indicate power status, and HDD activity
- Supports 400W~600W single PS/2 ATX power supply

### Introduction

Industrial MicroATX Motherboard Compact Chassis supports Standard uATX or Mini ITX Motherboard. SC-M604R3 can support up to 3 Drives. Single 9cm system cooling fan allows maximum ventilation for the system to function at its peak.

SC-M604R2 supports only Standard PS/2 Power Supply. Suitable for Factory Automation Application, Machine Automation, Military Application and Industrial / Telecom Computers

### Specification

System	
Drive bays	Totally 3 drive bay: 2x 5.25" External and 1 x 3.5" Internal HDD bay Drive bay equipped with anti-vibration function
Front Panel	Two USB 2.0 ports at front bezel
Motherboard	uATX or Mini ITX Motherboard
Fan	One 90mm intake fan
Power Supply	PS/2 ATX Power Supply
Expansion	4 Slot for uATX Motherboard
Color	Beige/Black
Dimension	275(D) x 410(W) x 175(H)mm
Weight	N.W: 8.1 KG.W:9.1 KGS
Mechanical & Environment	
Operating Temperature	0°~50°C
Storage Temperature	-40°~70°C
Relative Humidity	5~95%, non-condensing
Storage Humidity	5% ~ 95%
Altitude	10,000 Feet (3000 m)
Vibration (Operating)	1.5G Max
Shock	10G peak acceleration (10Msec duration)
Ordering Information	
SC-M604R3-C0	Industrial uATX Motherboard Compact Chassis (Color:Beige)
SC-M604R3-C1	Industrial uATX Motherboard Compact Chassis (Color:Black)
Optional	
TCPS1D41Y060	Industrial 600W ATX PS/2 Auto Ranging Power Supply
TCPS1D41Y050	Industrial 500W ATX PS/2 Auto Ranging Power Supply
TCPS1D41Y040	Industrial 400W ATX PS/2 Auto Ranging Power Supply

### Dimension

