I-View K1760

1U 19" Rack Mount 17" LCD, keyboard / Touchpad, PS/2 or USB channel Single Port KVM



Features

FC

Rear View

- 1U design consists of 17" LCD monitor, keyboard and mouse
- Connect to a server or KVM switch via a standard VGA connector
- 17" TFT LCD monitor with highlight, high definition and high resolution
- Integrated touchpad with trackball
- Multi-platform Support-Compatible with Windows, Sun, Unix and Linux
- Supports server form Lenovo, HP, IBM, Cisco and Dell
- Full size 99 keys keyboard with integrated number pad Cable allows for connection to a USB/PS2 computer or KVM

Introduction

Specification Model

Connections

Port Emulation

Compatibility

LCD Monitor

Direct Max

Multi-platform

LCD Mode

View Area

The I-View K1760 is a rack mount LCD KVM Console that features an integrated 17" LCD monitor, full keyboard and touchpad in a 1U compact design. The included cable allows for connection to a USB/PS2 computer or KVM. This console supports resolution up to 1280x1024@60Hz.

K1760

PS/2, USB

SXGA TFT

17"

1 DB15 Female (blue)

Windows, Sun, Unix, Linux

1 . 🚟
Connection Diagram
🔟 F 🔹 🚎
PC
Cables
CBL-1801M CBL-1802U CBL-3001M CBL-3001U
CBL-5001M CBL-5001U Dimension
• 4465
481

SINETIC Technologies Inc, reserves the right to change or update without notice, any information contained herein; to change without notice, the design construction, materials, processing or specifications of any products and to discontinue or limit production or distribution or of any products. © 2020 SINETIC Technologies Inc. All rights reserved. DMIVIEWK1760 Rev 1.0 Dated 202004.

	Resolution	1280x1024@60Hz
	Display color	16.7 M
	Brightness	250cd/m ² (Typ)
	Contrast Ratio	1000: 1 (Typ)
	Pixel pitch (mm)	0.264(H) x 0.264(W)
Input Power		100V-240V (AC), 50-60Hz, <1.5 A
Optional Power	Input	-36V – 72V DC
Power Consum	otion	13W
Emulation	Keyboard	99 keys (82 keys main keyboard + 17 keys independent small number pad) <i>Multi-language support</i> English, Russian, German, French, Korean, Swedish and Italian, etc
	Mouse	X/Y resolution (>1000 points/inch) Supports trackball function
Environment Requirement	Operating Temp	0 - 40 °C
	Storage Temp	-20 – 60 °C
	Humidity	0-80% RH (non-condensing)
Mechanical Features	Material	SECC
	Weight	11.7kg
	Dimension	448mm x 481mm x 42.5mm
Packaging Cont	ent	
 1x I-VIEW 	K1760 LCD Console	
 1y Power C 	ord (Regional)	

- 1x Power Cord (Regional)
- 2x Mounting Rails
- 1x USB+VGA KVM Cable (1.8m/6ft)
 1x Quick Start Guide

Ordering Information				
I-View K1760	1U 19" Rack Mount 17" LCD, keyboard /TouchPad, PS/2 or			
	USB channel Single Port KVM			
Packaging	765mm x 615mm x 185mm			
Dimension				
Optional				
CBL-1801M	1.8 Meter KVM Cable Combo (PS/2 & USB) (Default)			
CBL-1802U	1.8 Meter KVM Cable Combo (USB)			
CBL-3001M	3 Meter KVM Cable Combo (PS/2 & USB)			
CBL-3001U	3 Meter KVM Cable Combo (PS/2)			
CBL-5000M	5 Meter KVM Cable Combo (PS/2 & USB)			
CBL-5001U	5 Meter KVM Cable Combo (PS/2)			