

Self-Service Solutions Application with Embedded Box PC and Touch Monitors

**EMPOWERING
SELF-SERVICE SOLUTIONS**

Self-Ordering & Checkout *Patient Registration* *Ticketing & Travel* *Industrial Control*

Embedded Box PCs | Touchscreen Monitors | Reliable & Secure | 24/7 Operation

1. Solution Overview

A Self-Service Solution integrates:

- Embedded Box PC (industrial-grade computing unit)
- Touch Monitor (Interactive Display)
- Optional peripherals (printer, scanner, payment terminal, camera, NFC, etc.)
- Custom self-service software application
-

This system enables customers or users to independently perform transactions, check-ins, ordering, registration, payments, or information retrieval — reducing manpower dependency and improving operational efficiency.

2. System Architecture

A. Hardware Layer

Embedded Box PC

An industrial, compact computing unit designed for 24/7 operation.

Key Features:

- Fanless design (dust-resistant, low maintenance)
- Industrial-grade CPU (Intel / AMD / ARM)
- Wide voltage input (9–36V DC typical)
- Extended temperature support
- Multiple I/O ports (USB, COM, LAN, HDMI/DP)

Functions:

- Runs the self-service application
- Controls peripherals
- Manages network communication
- Handles local processing and caching

Touch Monitor

Interactive display for user input and interface presentation.

Types:

- Capacitive touch (PCAP) – high sensitivity, multi-touch
- Resistive touch – glove-friendly (industrial use)
- Open-frame / Panel-mount / VESA mount

Sizes:

- 10" – 15" (compact kiosks)
- 15.6" – 21.5" (standard kiosks)
- 27"+ (large interactive systems)

Features:

- Multi-touch support
- Anti-glare glass
- Waterproof front (IP65 optional)
- Tempered glass for durability

Optional Peripherals

Depending on the application:

- QR/Barcode Scanner
- RFID/NFC Reader
- Receipt Printer
- Thermal Label Printer
- Payment Terminal (EMV, contactless)
- Camera (Face recognition, security)
- Microphone & Speaker
- Card Dispenser / Ticket Dispenser

3. Software Architecture

A. Application Layer

The self-service software typically includes:

- User Interface (Touch-optimized UI/UX)
- Workflow Engine (Step-by-step process)
- Payment Integration
- Device Integration Layer
- API Integration with backend systems

B. Backend Integration

Connected to:

- ERP systems
- POS systems
- CRM systems
- Hospital Management Systems
- Inventory systems
- Cloud dashboards
- Payment gateways

Communication via:

- REST APIs
- WebSocket
- MQTT
- Local SDK integration

C. OS Options

- Windows IoT Enterprise
- Linux (Ubuntu, Debian)
- Android (for lightweight deployments)

4. Key Application Use Cases

Retail

- Self-checkout kiosks
- Product lookup
- Membership registration

F&B

- Self-ordering kiosk
- Table ordering system
- Queue management

Healthcare

- Patient registration
- Appointment check-in
- Payment kiosk

Hospitality

- Hotel self check-in/out
- Visitor management
- Digital concierge

Industrial

- Machine control interface (HMI)
- Access control terminal
- Production data entry terminal

5. Benefits of Embedded Box PC + Touch Monitor Architecture

Reliability

- Industrial-grade components
- Designed for 24/7 operation

Modular Design

- Replace monitor or PC independently
- Easy maintenance

Scalability

- Add peripherals easily
- Upgrade software without hardware change

Cost Efficiency

- Lower manpower requirement
- Reduced queue time
- Increased transaction throughput

Customizability

- Fully customizable UI
- Brand-specific design
- Configurable workflows

6. Deployment Models

Standalone Kiosk

- Integrated enclosure
- Public-facing deployment

Wall-Mounted Terminal

- Space-saving
- Hospitals / Factories

Countertop Unit

- Retail / F&B

Industrial Panel PC Alternative

- Box PC mounted behind panel touch monitor

7. Security Considerations

- Secure Boot
- TPM 2.0
- Disk encryption
- BIOS lock
- Kiosk mode lockdown
- Network firewall
- Remote device management
- Automatic OS recovery

8. Remote Management & Monitoring

Enterprise deployments often include:

- Remote monitoring dashboard
- Device health status
- Remote updates (OTA)
- Log monitoring
- Auto reboot scheduling
- Alert notifications

9. Typical Technical Specifications (Example)

Embedded Box PC:

- Intel Celeron / Core i3 / i5
- 8GB RAM
- 128GB SSD
- Dual LAN
- 4–6 USB ports
- HDMI + DisplayPort

Touch Monitor:

- 15.6" PCAP multi-touch
- 1920x1080 resolution
- 7H tempered glass
- IP65 front panel
- VESA 75/100 mount

10. Future Enhancements

- AI-powered recommendations
- Facial recognition login
- Voice interaction
- Cloud-based analytics
- Edge AI computing
- IoT device integration