

PPC-SH215-8000

Industrial 21.5" LCD Fanless Panel PC with Intel 8th Generation Processor, 4 USB Ports/ 6 COM Ports/ HDMI / Dual Gigabit LAN



FEATURES

- Intel® 8th Generation processor with graphics built in.
- Max memory: DDR3 up to 16GB
- Dual Gigabit Ethernet Ports
- Intel® Integrated HD Graphics Technology
- Realtek® ALC662 High-Definition Audio chip on-board
- Multi I/O: 3x USB 2.0 & 1 x USB3.0, 6x COM ports
- Bay: 1x 2.5" HDD (Internal) Bays
- Input Power: 12V DC
- Front Bezel Protection: IP65
- Supported OS: Windows® 8/10, Linux, Ubuntu, Debian

Introduction

PPC-SH215-8000 Industrial Panel PC supporting Intel 8th Generation Processor with Built in Graphics. PPC-SH215-8000 comes with 21.5" LCD Display. PPC-SH215-8000 supports One 2.5" HDD/SSD, 2x Com Port, 2 x USB 3.0 & 2 USB 2.0 Ports and one Mini PCIe expansion slot.

PPC-SH215-8000 is ideal for developing high-performance systems for industrial control and Automation, retail, gaming, print imaging and digital signage.

Specification

LCD	
Model	PPC-SH215-8000
Resolution	1920x1080 FHD
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Viewing Angle	170/170
Backlight	LED
Backlight MTBF	35000Hrs
Touch Screen	
Touchscreen Type	Project Capacitive Touch (10 points)
Touchscreen Interface	USB
Touch response time	2ms
Luminousness	90%
Surface Hardness	7H
MTBF	>50 million times
System	
Processor	<ul style="list-style-type: none"> • Intel® Core, i7-8550U, quad core, 1.8GHz, fanless • Intel® Core, i5-8250U, quad core, 1.6GHz, fanless
BIOS	• AMI
System Memory	• Max. 16GB
Chipset	• -
Video	<ul style="list-style-type: none"> • Integrated graphics HD Graphics • One HDMI
Ethernet	<ul style="list-style-type: none"> • Dual Realtek RTL 8111E Gigabit Ethernet controller • One Wifi Module (Optional)
On Board I/O	<ul style="list-style-type: none"> • 3x USB 2.0 Ports • 1x USB 3.0 Ports • 6 x COM RS232 Ports (COM1~COM 2 RS-232/422/485 & COM3~COM6 3 Wire RS-232)
Watchdog Timer	• Programmable watchdog timer for 1~255 seconds.
CMOS	• On-board RTC with 242 bytes of Battery-back CMOS RAM.
Audio	<ul style="list-style-type: none"> • Realtek ALC662, High Definition Audio (HD) • Support Line-OUT, MIC
Power	• Support both AT and ATX mode.
Cooling	<ul style="list-style-type: none"> • One CPU cooling FAN connector nearby CPU socket • One system cooling FAN connectors for chassis or power supply cooling.
Power Requirement	
External Power	AC 100~240V
Power Input	9V ~36V DC
Power Consumption	~40W
Mechanical & Environment	
Drive Bay	• One 2.5" Hard Disk Bay
Dimension	• 534.4(W) x 328(H) x 62.1(D) mm
Weight	• Gross 9.8kg, NW 8Kg
Operation temperature	• -20 to 60°C
Storage temperature	• -30 to 70°C
Relative humidity	• 5% to 95% (Non-Condensing)
Vibration	• 5-500 Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Additional Chassis FAN	• N/A
Front Bezel protection	• IP65 Compliant

Ordering Information

PPC-SH215-8550-C109	Industrial 21.5" LCD Fanless Panel PC with Intel 8 th Generation i7-8550U Processor, 4 USB Ports/ 6 COM Ports/ HDMI / Dual Gigabit LAN
PPC-SH215-8250-C109	Industrial 21.5" LCD Fanless Panel PC with Intel 8 th Generation i5-8250U Processor, 4 USB Ports/ 6 COM Ports/ HDMI / Dual Gigabit LAN

Dimension

